

# FloorMatte™

## NON-GLARE FLOOR COATING

An ultra low sheen finish for applications where low gloss levels are desired.



### WHY FLOORMATTE FLOOR COATING:

#### IDEAL FOR NO-BURNISH AND/OR ELDERCARE APPLICATIONS

Low sheen

#### HIGHLY RESISTANT TO SCUFF AND BLACK HEEL MARKS

Durable polymer and wax blend

### TECHNICAL DATA

Description	Polymer emulsion
Appearance	Milky white
Specular Gloss (60°) ASTM D1455-87 (2008)	<35
Viscosity (Brookfield) (@ 68°F (20°C))	<10 centipoise
Coverage Rate	2500 to 3000 ft <sup>2</sup> /gal 61 to 74 m <sup>2</sup> /liter
Dry Time	About 30 minutes
Removability ASTM D1792-06	Good
VOC 40 CFR Part 59 Subpart C	0.02%
Total Solids	22%
Non-Volatile Solids ASTM D2834-95 (2008)	16%
Fragrance	Mild odor
Slip Resistance ULTM410	Meets requirements
Shelf Life ASTM D1791-93 (2008)	1 year
Density ASTM D1475-98 (2008)	8.5 lb/gal @ 68°F 1.02 kg/L @ 20°C
Detergent Resistance ASTM D3207-92 (2008)	Excellent
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

SURFACES



#### DISINFECTANT COMPATIBILITY:

The following Pioneer Eclipse disinfectants are safe to use on this floor coating when correctly diluted and used according to the product directions. Bleach and other corrosives may cause damage.

Nova Disinfectant

MeridiClean All Purpose Cleaner & Disinfectant

NeutraQuat 256 Germicidal Disinfectant

Triton XLC Bathroom Cleaner & Disinfectant

### DIRECTIONS

Apply thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at [pioneereclipse.com](http://pioneereclipse.com)



Floor Coating and Finishing materials  
as to slip resistance only.

42E6

Product Code	114FS
Volume	2.50 US gallons
Shipping Package	2 x 2.5 gallons
Pallet Quantity	48