

# Equinox HG™

## ULTRA HIGH SPEED FLOOR COATING

A highly durable UHS finish with excellent off-the-mop gloss for an immediate shine.



SURFACES



### WHY EQUINOX HG:

## HIGH GLOSS BURNISH RESPONSE

Advanced acrylic co-polymer technology

## EASY STRIPPING SAVES TIME AND LABOR

## REPAIRABLE AND DURABLE - RESISTS WEAR AND SCUFF MARKS

Durable wax blend

### TECHNICAL DATA

Description	Polymer emulsion
Appearance	Milky white
Specular Gloss (60°) ASTM D1455-87 (2008)	>80
Viscosity (Brookfield) (@ 68°F (20°C))	<10 centipoise
Coverage Rate	2500 to 3000 ft²/gal 61 to 74 m²/liter
Dry Time	About 25 minutes
Buffability	Excellent
Removability ASTM D1792-06	Excellent
VOC 40 CFR Part 59 Subpart C	0.06%
Total Solids	28%
Non-Volatile Solids ASTM D2834-95 (2008)	22%
Fragrance	Slight ammoniated
Slip Resistance ULTM410	Meets requirements
Shelf Life ASTM D1791-93 (2008)	1 year
Density ASTM D1475-98 (2008)	8.5 lb/gal @ 68°F 1.02 kg/L @ 20°C
Detergent Resistance ASTM D3207-92 (2008)	Excellent
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

### DISINFECTANT COMPATIBILITY:

The following Pioneer Eclipse disinfectants are safe to use on this floor coating when correctly diluted and used according to the product directions. Bleach and other corrosives may cause damage.

Nova Disinfectant

MeridiClean All Purpose Cleaner & Disinfectant

NeutraQuat 256 Germicidal Disinfectant

Triton XLC Bathroom Cleaner & Disinfectant

### DIRECTIONS

Apply thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at [pioneereclipse.com](http://pioneereclipse.com)



Floor Coating and Finishing materials as to slip resistance only. 42E6

Product Code	139FS	139MPE	139DR
Volume	2.50 US gallons	4 liters	55 US gallons
Shipping Package	2 x 2.5 gallons	4 x 4 liters	1 x 55 gallons
Pallet Quantity	48	48	4