

# OmniGuard™

## ULTRA HIGH SPEED FLOOR COATING

A high solids finish with a superior gloss level that is ideal for use in retail facilities, or other high traffic areas.



No Intentionally  
Added PFAS

SURFACES



### WHY OMNIGUARD:

## HIGH GLOSS BURNISH RESPONSE

Advanced Acrylic Co-Polymer

## REPAIRABLE AND DURABLE

Wax blend with superior buff response to fix scratches and wear patterns

## LABOR SAVING

25% Solids

### TECHNICAL DATA

Description	Polymer emulsion
Appearance	Milky white
Specular Gloss (60°)	>85
ASTM D1455-87 (2008)	
Viscosity (Brookfield)	<10 centipoise
@ 68°F (20°C)	
Coverage Rate	2500 to 3000 ft <sup>2</sup> /gal 61 to 74 m <sup>2</sup> /liter
Dry Time	About 25 minutes
Buffability	Excellent
Removability	Excellent
ASTM D1792-06	
VOC	0.06%
40 CFR Part 59 Subpart C	
Non-Volatile Solids	25%
ASTM D2834-95 (2008)	
Fragrance	Mild odor, no fragrance added
Slip Resistance	UL pending
ULTM410	
Shelf Life	1 year
ASTM D1791-93 (2008)	
Density	8.5 lb/gal @ 68°F 1.03 kg/L @ 20°C
ASTM D1475-98 (2008)	
Detergent Resistance	Excellent
ASTM D3207-92 (2008)	
Freeze/Thaw	Passes 3 cycles
ASTM D3209-93 (2008)	

#### DISINFECTANT COMPATIBILITY:

The following Pioneer Eclipse disinfectants are safe to use on this floor coating when correctly diluted and used according to the product directions. Bleach and other corrosives may cause damage.

Nova Disinfectant  
MeridiClean All Purpose Cleaner & Disinfectant  
NeutraQuat 256 Germicidal Disinfectant  
Triton XLC Bathroom Cleaner & Disinfectant

### DIRECTIONS

Porous floors or high traffic areas - Apply 2 thin coats of floor sealer

Apply thin coats of OmniGuard using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at [pioneereclipse.com](http://pioneereclipse.com)



UL pending 4ZE6

Product Code	141FS	141MPE	141DR
Volume	2.50 US gallons	4 liters	55 US gallons
Shipping Package	2 x 2.5 gallons	4 x 4 liters	1 x 55 gallons
Pallet Quantity	48	48	4

Note: Use product code 1410 to order with AMP additive

141\_PDS 09/25