

OmniGuard™

ULTRA HIGH SPEED FLOOR COATING

A high solids finish with a superior gloss level that is ideal for use in retail facilities, or other high traffic areas.



SURFACES



WHY OMNIGUARD:

HIGH GLOSS BURNISH RESPONSE

Advanced Acrylic Co-Polymer

REPAIRABLE AND DURABLE

Wax blend with superior buff response to fix scratches and wear patterns

LABOR SAVING

25% Solids

AMP™ ANTIMICROBIAL PROTECTION

Technology that inhibits the growth of bacteria on the floor surface

TECHNICAL DATA

Description	Polymer emulsion
Appearance	Milky white
Specular Gloss (60°) <small>ASTM D1455-87 (2008)</small>	>85
Viscosity (Brookfield) <small>@ 68°F (20°C)</small>	<10 centipoise
Coverage Rate	2500 to 3000 ft ² /gal 61 to 74 m ² /liter
Dry Time	About 25 minutes
Buffability	Excellent
Removability <small>ASTM D1792-06</small>	Excellent
VOC <small>40 CFR Part 59 Subpart C</small>	0.06%
Non-Volatile Solids <small>ASTM D2834-95 (2008)</small>	25%
Fragrance	Mild odor, no fragrance added
Slip Resistance <small>ULTM410</small>	UL pending
Shelf Life <small>ASTM D1791-93 (2008)</small>	1 year
Density <small>ASTM D1475-98 (2008)</small>	8.5 lb/gal @ 68°F 1.03 kg/L @ 20°C
Detergent Resistance <small>ASTM D3207-92 (2008)</small>	Excellent
Freeze/Thaw <small>ASTM D3209-93 (2008)</small>	Passes 3 cycles

DISINFECTANT COMPATIBILITY:

The following Pioneer Eclipse disinfectants are safe to use on this floor coating when correctly diluted and used according to the product directions. Bleach and other corrosives may cause damage.

Nova Disinfectant
MeridiClean All Purpose Cleaner & Disinfectant
NeutraQuat 256 Germicidal Disinfectant
Triton XLC Bathroom Cleaner & Disinfectant

DIRECTIONS

Porous floors or high traffic areas - Apply 2 thin coats of floor sealer

Apply thin coats of OmniGuard using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com



UL pending

42E6

Product Code	1410FS	1410MPE	1410DR
Volume	2.50 US gallons	4 liters	55 US gallons
Shipping Package	2 x 2.5 gallons	4 x 4 liters	1 x 55 gallons
Pallet Quantity	48	48	4

1410_PDS 07/23

AMP™ AntiMicrobial Protection is a chemical technology in select Pioneer Eclipse floor coatings that inhibits the growth of bacteria.

Bacteria on floors is a common source of odor and stains. **AMP** is an EPA registered ingredient within the floor coating that inhibits the growth of stain and odor causing bacteria on the floor surface.



**INHIBITS THE
GROWTH OF BACTERIA**



**CONTINUOUS
ANTIMICROBIAL
PROTECTION 24/7**



**REDUCES
ODORS & STAINS**



**EPA REGISTERED
ANTIMICROBIAL
INGREDIENT**

Pioneer Eclipse floor coatings with **AMP** technology provide continuous antimicrobial protection from the moment the floor coating is dry, 24/7 for the usable life of the coating. No chemical mixing or non-standard floor preparation is required. This unique application of technology inhibits the growth of odor and stain causing bacteria on a cellular level, preventing bacterial microorganisms from feeding, growing, and reproducing.

The application of floor coatings with AMP technology is not a substitute for normal cleaning practices.