

Lumen L142™

FLOOR COATING/SEALER

A durable floor coating option with a “wet look” that lasts.



SURFACES



WHY LUMEN L142:

HIGH GLOSS BURNISH RESPONSE

Advanced Acrylic Co-Polymer

REPAIRABLE AND DURABLE

Wax blend with excellent buff response to fix scratches and wear patterns

TECHNICAL DATA

Description	Polymer emulsion
Appearance	Milky white
Specular Gloss (60°) <small>ASTM D1455-87</small>	>85
Viscosity (Brookfield) <small>@ 68°F (20°C)</small>	<10 centipoise
Coverage Rate	2500 to 3000 ft²/gal 61 to 74 m²/liter
Dry Time	About 25 minutes
Buffability	Excellent
Removability <small>ASTM D1792-17</small>	Excellent
VOC <small>40 CFR Part 59 Subpart C</small>	<0.1%
Fragrance	Mild odor, no fragrance added
Slip Resistance <small>ULTM410</small>	ULTM410 Pending
Shelf Life <small>ASTM D1791-93</small>	1 year
Density <small>ASTM D1475-13</small>	8.5 lb/gal @ 68°F 1.02 kg/L @ 20°C
Detergent Resistance <small>ASTM D3207-17</small>	Excellent
Freeze/Thaw <small>ASTM D3209-93</small>	Passes 3 cycles

DISINFECTANT COMPATIBILITY:

The following Pioneer Eclipse disinfectants are safe to use on this floor coating when correctly diluted and used according to the product directions. Bleach and other corrosives may cause damage.

MeridiClean All Purpose Cleaner & Disinfectant

NeutraQuat 256 Germicidal Disinfectant

Triton XLC Bathroom Cleaner & Disinfectant

DIRECTIONS

Porous floors or high traffic areas - Apply 2 thin coats of floor sealer

Apply thin coats of Lumen L142 using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com

Product Code	142FS	142MPE
Volume	2.50 US gallons	4 Liters
Shipping Package	2 x 2.5 gallons	4 x 4L
Pallet Quantity	48	48