

Orion 25™

LOW MAINTENANCE FLOOR COATING

A high solids, high gloss, low maintenance finish formulated to significantly reduce the need for re-coating and burnishing.



WHY ORION 25:

**FEWER COATS NEEDED
= LABOR SAVINGS**

25% Solids

**HIGH GLOSS LEVEL WITHOUT
FREQUENT BURNISHING**

Acrylic co-polymer blend

**REPAIRABLE, RESISTS DIRT
EMBEDDING IN FINISH**

**HIGHLY RESISTANT TO SCUFF AND
BLACK HEEL MARKS**

Durable polymer and wax blend

AMP™ ANTIMICROBIAL PROTECTION

Technology that fights the growth of bacteria on the floor surface

DIRECTIONS

Apply thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com

TECHNICAL DATA

Description	Polymer emulsion
Appearance	Milky white
Specular Gloss (60°) ASTM D1455-87 (2008)	>80
Viscosity (Brookfield) (@ 68°F (20°C))	<10 centipoise
Coverage Rate	2500 to 3000 ft ² /gal 61 to 74 m ² /liter
Dry Time	About 30 minutes
Buffability	Excellent
Removability ASTM D1792-06	Excellent
VOC 40 CFR Part 59 Subpart C	0.02%
Total Solids	32%
Non-Volatile Solids ASTM D2834-95 (2008)	25%
Fragrance	Mild odor
Slip Resistance ULTM410	UL pending
Shelf Life ASTM D1791-93 (2008)	1 year
Density ASTM D1475-98 (2008)	8.6 lb/gal @ 68°F 1.03 kg/L @ 20°C
Detergent Resistance ASTM D3207-92 (2008)	Excellent
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

CARB
Compliant

SURFACES



DISINFECTANT COMPATIBILITY:

The following Pioneer Eclipse disinfectants are safe to use on this floor coating when correctly diluted and used according to the product directions. Bleach and other corrosives may cause damage.

Nova Disinfectant

MeridiClean All Purpose Cleaner & Disinfectant

NeutraQuat 256 Germicidal Disinfectant

Triton XLC Bathroom Cleaner & Disinfectant

Product Code	148FS	148MPE
Volume	2.50 US gallons	4 liters
Shipping Package	2 x 2.5 gallons	4 x 4 liters
Pallet Quantity	48	48