

ReBounce™

FLOOR CLEANER & ENHANCER



An effective daily cleaner and enhancer that extends the life of the coating and leaves a brilliant wet-look shine.

WHY REBOUNCE FLOOR CLEANER & ENHANCER:

EXTENDS THE LIFE OF THE COATING

Wax fortified formulation

HELPS MAINTAIN COATING ELASTICITY, PREVENT CRACKS AND CHIPS

Wax fortified formulation

ENHANCES BURNISH RESPONSE — GLOSS “POPS” BACK

High performance pH-balanced surfactant

EFFECTIVELY REMOVES DIRT AND SCUFFS

DIRECTIONS

Apply thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com

TECHNICAL DATA

Description Water-based cleaner/enhancer

Appearance Clear green

pH 9.0 (as supplied)
ASTM E70-07 DTC/DD: 10.5 (as supplied)

Viscosity (Brookfield) <10 centipoise
@ 68°F (20°C)

Dry Time About 15 minutes

VOC 0.01% (as supplied)
40 CFR Part 59 Subpart C <0.01% (1:32 dilution)
<0.01% (1:128 dilution)
DTC/DD: 0.02% (as supplied)

Non-Volatile Solids 11%
ASTM D2834-95 (2008) DTC/DD: 46%

Fragrance Lemon-Lime

Slip Resistance Meets requirements
ULTM410

Shelf Life 1 year
ASTM D1791-93 (2008)

Density 8.4 lb/gal @ 68°F
ASTM D1475-98 (2008) 1.01 kg/L @ 20°C
DTC/DD: 8.6 lb/gal @ 68°F
DTC/DD: 1.03 kg/L @ 20°C

Freeze/Thaw Passes 3 cycles
ASTM D3209-93 (2008)



Floor Coating and Finishing materials as to slip resistance only. 42E6

SURFACES



Product Code	211FS	211MPE	211DTC	211D	211DD
Volume	2.50 US gallons	4 liters	.053 US gallon	1.06 US gallons	0.50 US gallon
Shipping Package	2 x 2.5 gallons	4 x 4 liters	4 x 0.53 gallons	4 x 1.06 gallons	3 x 0.50 gallons
Pallet Quantity	48	48	88	48	112