

PrimeStar™

BASE COAT

Removable high solids sealer for VCT, to help build gloss quickly.



SURFACES



VCT

WHY PRIMESTAR BASE COAT:

FILLS GAPS IN POROUS FLOORS

Acrylic co-polymer blend

LABOR SAVINGS

22% solids, fewer coats needed

TECHNICAL DATA

Description	Polymer emulsion
Appearance	Milky white
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise
Coverage Rate	1500 ft ² /gal first coat 37 m ² /l 2500 to 3000 ft ² /gal 61 to 74 m ² /liter
Dry Time	20 - 25 minutes
Removability ASTM D1792-06	Excellent
VOC 40 CFR Part 59 Subpart C	0.04%
Non-Volatile Solids ASTM D2834-95 (2008)	22%
pH ASTM E70-07	8.7
Fragrance	Slight ammoniated
Slip Resistance ULTM410	Meets requirements
Shelf Life ASTM D1791-93 (2008)	1 year
Density ASTM D1475-98 (2008)	8.6 lb/gal @ 68°F 1.03 kg/L @ 20°C
Detergent Resistance ASTM D3207-92 (2008)	Excellent
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

DIRECTIONS

Apply thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com



Floor Coating and Finishing materials
as to slip resistance only. 42E6

Product Code	409FS	409MPE
Volume	2.50 US gallons	4 liters
Shipping Package	2 x 2.5 gallons	4 x 4 liters
Pallet Quantity	48	48