



# EnviroStar™

## FLOOR SEALER

An environmentally preferred high solids sealer.



### WHY ENVIROSTAR FLOOR SEALER:

#### LABOR SAVINGS

22% Solids, fewer coats needed

#### ENVIRONMENTALLY PREFERRED

Zinc free

### TECHNICAL DATA

**Description** Water-based floor sealer

**Appearance** Milky white

**Viscosity (Brookfield)** <10 centipoise  
@ 68°F (20°C)

**Coverage Rate** 2000 to 2500 ft<sup>2</sup>/gal  
49 to 61 m<sup>2</sup>/liter

**Dry Time** About 30 minutes

**Removability** Excellent  
ASTM D1792-06

**VOC** 0.03%  
40 CFR Part 59 Subpart C

**Non-Volatile Solids** 22%  
ASTM D2834-95 (2008)

**pH** 8.0  
ASTM E70-07

**Fragrance** Mild odor, no added fragrance

**Shelf Life** 1 year  
ASTM D1791-93 (2008)

**Density** 8.6 lb/gal @ 68°F  
1.03 kg/L @ 20°C  
ASTM D1475-98 (2008)

**Detergent Resistance** Excellent  
ASTM D3207-92 (2008)

**Freeze/Thaw** Passes 3 cycles  
ASTM D3209-93 (2008)



**CARB**  
Compliant

SURFACES

VCT

TERRAZZO  
(CEMENTITIOUS)

MARBLE

CONCRETE

QUARRY TILE

### DIRECTIONS

Apply thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at [pioneereclipse.com](http://pioneereclipse.com)

|                  |                 |              |
|------------------|-----------------|--------------|
| Product Code     | 413FS           | 413MPE       |
| Volume           | 2.50 US gallons | 4 liters     |
| Shipping Package | 2 x 2.5 gallons | 4 x 4 liters |
| Pallet Quantity  | 48              | 48           |

413\_PDS 08/23