



CLS TopShield™

STAIN RESISTANT FLOOR PROTECTOR

A high performance, penetrating surface treatment that resists stains and enhances gloss.



SURFACES



WHY CLS TOPSHIELD:

UNIQUE SILICATE BLEND CREATES A SURFACE THAT IS:

- BREATHABLE
- ULTRA-HARD
- WATER/DUST REPELLENT

GUARDS AGAINST STAINS

CAN BE BURNISHED TO A HIGH GLOSS

TECHNICAL DATA

Description	Stain Resistant Floor Protector
Appearance	Milky white
pH ASTM E70-07	11.0
Flash Point	>200°F (93°C)
Viscosity (Brookfield) (@ 68°F (20°C))	<10 centipoise
Coverage Rate	3500 ft ² / gal 86 m ² /liter
VOC 40 CFR Part 59 Subpart D	<50 g/L
Fragrance	No added fragrance
Density ASTM D1475-13 (2008)	9.2 lb/gal @ 68°F 1.1 kg/l @ 20°C

DIRECTIONS

Apply with a pump-up sprayer. Spread evenly with a clean micro-fiber applicator. Allow to dry thoroughly and burnish with a hair blend pad. Repeat with a second coat.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com

Product Code	421FS
Volume	2.50 US gallons
Shipping Package	2 x 2.50 gallons
Pallet Quantity	48

421_PDS 06/24