

# TopShield™

## STAIN RESISTANT FLOOR PROTECTOR

A high performance, penetrating surface treatment that resists stains and enhances gloss.



No Intentionally  
Added PFAS

SURFACES



### WHY TOPSHIELD:

UNIQUE SELF-CROSSLINKING POLYMER BLEND  
CREATES A SURFACE THAT IS:

- BREATHABLE
- ULTRA-HARD
- WATER/DUST REPELLENT

LOW ODOR WATER-BASED FORMULA

Non-yellowing and UV stable

VERY FINE (SMALL) PARTICLE SIZE FOR BETTER  
SUBSTRATE PENETRATION

CAN BE BURNISHED TO A HIGH GLOSS

Maintains slip resistance.

FAST DRYING, EASY TO APPLY

### TECHNICAL DATA

<b>Description</b>	Stain Resistant Floor Protector
<b>Appearance</b>	Milky white
<b>pH</b> ASTM E70-07	11.0
<b>Flash Point</b>	>200°F (93°C)
<b>Viscosity (Brookfield)</b> @ 68°F (20°C)	<10 centipoise
<b>Coverage Rate</b>	3500 ft <sup>2</sup> / gal 86 m <sup>2</sup> /liter
<b>VOC</b> 40 CFR Part 59 Subpart D	<50 g/L
<b>Fragrance</b>	No added fragrance
<b>Density</b> ASTM D1475-13 (2008)	9.2 lb/gal @ 68°F 1.1 kg/l @ 20°C
<b>Shelf Life</b>	1 year

### DIRECTIONS

Apply with a pump-up sprayer. Spread evenly with a clean micro-fiber applicator. Allow to dry thoroughly and burnish with a hair blend pad. Repeat with a second coat.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at [pioneereclipse.com](http://pioneereclipse.com)

Product Code	421FS
Volume	2.50 US gallons
Shipping Package	2 x 2.50 gallons
Pallet Quantity	48