

Final Strip HD™

FLOOR STRIPPER



A non-ammoniated, economical floor stripper.

WHY FINAL STRIP HD™:

EFFECTIVE STRIPPING PERFORMANCE
Butyl-based

NON-AMMONIATED

TECHNICAL DATA

Description Non-ammoniated, ultra high performance stripper

Appearance Clear red

Viscosity (Brookfield) <5 centipoise
@ 68°F (20°C)

Flash Point >150°F (70°C)
ASTM D56-05 (2010)

VOC 33% (as supplied)
40 CFR PART 59 SUBPART C 2.94% (1:10)
3.59% (1:8)
6.48% (1:4)

Fragrance Slight lemon

Shelf Life 2 years
ASTM D1791-93 (2008)


Density 8.3 lb/gal @ 68°F
ASTM D1475 D-98 (2008) 0.99 kg/L @ 20°C

DIRECTIONS

Mix stripper per instructions for heavy, normal, or light coating removal.
Apply solution liberally to the floor and allow to soak — do not allow to dry.
Scrub floor with automatic scrubber or stripping machine.
Rinse thoroughly with clean water and allow floor to dry before applying finish.

Read all directions and Safety Data Sheet (SDS) before using.
Directions and SDS are available for download at pioneereclipse.com

SURFACES



Product Code	502FS	502MP
Volume	2.50 US gallons	1.06 US gallons
Shipping Package	2 x 2.5 gallons	4 x 1.06 gallons
Pallet Quantity	48	48