



# Final Strip HD™

## FLOOR STRIPPER



A non-ammoniated, economical floor stripper.

SURFACES



### WHY FINAL STRIP HD™:

**EFFECTIVE STRIPPING PERFORMANCE**  
Butyl-based

**NON-AMMONIATED**

### TECHNICAL DATA

**Description** Non-ammoniated, ultra high performance stripper

**Appearance** Clear red

**Viscosity (Brookfield)** <5 centipoise  
@ 68°F (20°C)


**Flash Point** > 200 °F / > 93 °C  
ASTM D56-05 (2010)

**VOC** 33% (as supplied)  
40 CFR PART 59 SUBPART C 2.94% (1:10)  
3.59% (1:8)  
6.48% (1:4)

**Fragrance** Slight lemon

**Shelf Life** 2 years  
ASTM D1791-93 (2008)

**Density** 8.3 lb/gal @ 68°F  
ASTM D1475 D-98 (2008) 0.99 kg/L @ 20°C



### DIRECTIONS

Mix stripper per instructions for heavy, normal, or light coating removal.  
Apply solution liberally to the floor and allow to soak — do not allow to dry.  
Scrub floor with automatic scrubber or stripping machine.  
Rinse thoroughly with clean water and allow floor to dry before applying finish.

Read all directions and Safety Data Sheet (SDS) before using.  
Directions and SDS are available for download at [pioneereclipse.com](http://pioneereclipse.com)

Product Code	502FS	502MP
Volume	2.50 US gallons	1.06 US gallons
Shipping Package	2 x 2.5 gallons	4 x 1.06 gallons
Pallet Quantity	48	48

502\_PDS 03/24