

Formula X™

FLOOR STRIPPER

An ideal balance of powerful stripping performance and open time.



WHY FORMULA X FLOOR STRIPPER:

POWERFUL STRIPPING PERFORMANCE

Butyl-based

REDUCED ODOR WITH POWERFUL STRIPPING PERFORMANCE

Unique blend of actives

LONG OPEN TIME

TECHNICAL DATA

Description	Non-ammoniated, ultra high performance stripper Gel: clinging gel aerosol baseboard stripper
Appearance	Clear liquid Gel: Cloudy colorless liquid gel
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise
Flash Point ASTM D56-05 (2010)	150°F (66°C) Gel: N/A
VOC 40 CFR PART 59 SUBPART C	42% (as supplied) 2.42% (1:16) 4.57% (1:8) 8.24% (1:4)
Fragrance	Citrus
Shelf Life ASTM D1791-93 (2008)	2 years
Density ASTM D1475 D-98 (2008)	8.3 lb/gal @ 68°F 1.0 kg/L @ 20°C
Gel Vapor Pressure	60 psig @ 70°F (21°C)

DIRECTIONS

Mix stripper per instructions for heavy, normal, or light coating removal.
Apply solution liberally to the floor and allow to soak — do not allow to dry.
Scrub floor with automatic scrubber or stripping machine.
Rinse thoroughly with clean water and allow floor to dry before applying finish.
Read all directions and Safety Data Sheet (SDS) before using.
Directions and SDS are available for download at pioneereclipse.com

SURFACES



Product Code	503FS	503MP	503A12E
Volume	2.50 US gallons	1.06 US gallons	18 US ounces
Shipping Package	2 x 2.5 gallons	2 x 1.06 gallons	12 x 18 ounces
Pallet Quantity	48	48	72