

# Formula X™

## FLOOR STRIPPER

An ideal balance of powerful stripping performance and open time.



SURFACES



### WHY FORMULA X FLOOR STRIPPER:

#### POWERFUL STRIPPING PERFORMANCE

Butyl-based

#### REDUCED ODOR WITH POWERFUL STRIPPING PERFORMANCE

Unique blend of actives

#### LONG OPEN TIME

### TECHNICAL DATA

<b>Description</b>	Non-ammoniated, ultra high performance stripper Gel: clinging gel aerosol baseboard stripper
<b>Appearance</b>	Clear liquid Gel: Cloudy colorless liquid gel
<b>Viscosity (Brookfield)</b> @ 68°F (20°C)	<10 centipoise
<b>Flash Point</b> ASTM D56-05 (2010)	> 200 °F / > 93 °C Gel: N/A
<b>VOC</b> 40 CFR PART 59 SUBPART C	42% (as supplied) 2.42% (1:16) 4.57% (1:8) 8.24% (1:4)
<b>Fragrance</b>	Citrus
<b>Shelf Life</b> ASTM D1791-93 (2008)	2 years
<b>Density</b> ASTM D1475 D-98 (2008)	8.3 lb/gal @ 68°F 1.0 kg/L @ 20°C
<b>Gel Vapor Pressure</b>	60 psig @ 70°F (21°C)



### DIRECTIONS

Mix stripper per instructions for heavy, normal, or light coating removal.  
Apply solution liberally to the floor and allow to soak — do not allow to dry.  
Scrub floor with automatic scrubber or stripping machine.  
Rinse thoroughly with clean water and allow floor to dry before applying finish.

Read all directions and Safety Data Sheet (SDS) before using.  
Directions and SDS are available for download at [pioneereclipse.com](http://pioneereclipse.com)

<b>Product Code</b>	503FS	503FSC	503FSE	503MP	503MPE
<b>Volume</b>	2.50 US gallons	2.50 US gallons	10 liters	1.06 US gallons	4 liters
<b>Shipping Package</b>	2 x 2.5 gallons	2 x 2.5 gallons	2 x 10 liters	2 x 1.06 gallons	4 x 4 liters
<b>Pallet Quantity</b>	48	48	48	48	48

503\_PDS 07/24