

Flash 55™

FLOOR STRIPPER

Our most aggressive stripper for multiple coat removal and high-burnished finishes.



WHY FLASH 55 FLOOR STRIPPER:

OUR MOST AGGRESSIVE STRIPPER FOR ANY APPLICATION

55% actives content

EXCELLENT RESULTS EVEN AFTER NUMEROUS SCRUB AND RECOATS

PLEASANT FRAGRANCE

Floral

TECHNICAL DATA

Description Fast-acting floor stripper

Appearance Clear blue

Viscosity (Brookfield) <10 centipoise
@ 68°F (20°C)

Flash Point 150°F (66°C)
ASTM D56-05 (2010)


VOC 54.5% (as supplied)
40 CFR PART 59 SUBPART C 10.5% (1:4)
5.8% (1:8)

Fragrance Floral

Shelf Life 2 years
ASTM D1791-93 (2008)

Density 8.0 lb/gal @ 68°F
ASTM D1475 D-98 (2008) 0.96 kg/L @ 20°C

SURFACES



DIRECTIONS

Mix stripper per instructions for heavy, normal, or light coating removal.
Apply solution liberally to the floor and allow to soak — do not allow to dry.
Scrub floor with automatic scrubber or stripping machine.
Rinse thoroughly with clean water and allow floor to dry before applying finish.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com

Product Code	516FS	516MP	516DR
Volume	2.50 US gallons	1.06 US gallons	55 US gallons
Shipping Package	2 x 2.5 gallons	4 x 1.06 gallons	1 x 55 gallons
Pallet Quantity	48	48	4