

# EZ-Strip™

## LOW ODOR FLOOR STRIPPER

A powerful Low Odor Stripper with longer open time.



### WHY EZ-STRIP™ LOW ODOR FLOOR STRIPPER:

#### USE IN OCCUPIED SPACES

Low Odor

#### LONGER WORKING TIME

Extended Open Time

#### EFFECTIVE IN TOUGH APPLICATIONS

Butyl Formulation

### SPECIFICATIONS

**Description** Low odor stripper

**Appearance** Clear

**Viscosity (Brookfield)** <10 centipoise  
@ 68°F (20°C)

**Flash Point** >200°F (93°C)  
ASTM D56-05 (2010)

**VOC** 25.7% (as supplied)  
40 CFR PART 59 SUBPART C 5.1% (1:4)  
2.8% (1:8)

**pH** 12.5 (as supplied)  
ASTM E70-07

**Fragrance** None added

**Shelf Life** 2 years  
ASTM D1791-93 (2008)

**Density** 8.8 lb/gal @ 68°F  
ASTM D1475 D-98 (2008) 1.05 kg/L @ 20°C

**Freeze/Thaw** Passes 3 cycles  
ASTM D3209-93 (2008)

### DIRECTIONS

Mix stripper per instructions for heavy, normal, or light coating removal.

Apply solution liberally to the floor and allow to soak — do not allow to dry.

Scrub floor with automatic scrubber or stripping machine.

Rinse thoroughly with clean water and allow floor to dry before applying finish.

Read all directions and Safety Data Sheets (SDS) before using.

Detailed directions and SDS sheets available for download at [pioneereclipse.com](http://pioneereclipse.com)

SURFACES



<b>Product Code</b>	517FS	517MP
<b>Volume</b>	2.50 US gallons	4 liters
<b>Shipping Package</b>	2 x 2.50 gallons	4 x 4 liters
<b>Pallet Quantity</b>	48	48