

Helios H522™

FLOOR STRIPPER

A strong stripper specifically formulated for use on LVT and other low maintenance flooring



SURFACES



WHY HELIOS H522 FLOOR STRIPPER:

EXTRA STRENGTH STRIPPING PERFORMANCE

Strips without damaging or discoloring

TECHNICAL DATA

Description Floor stripper

Appearance Clear

Viscosity (Brookfield) <5 centipoise
(@ 68°F [20°C])

Flash Point >200°F (93°C)
ASTM D56-22

VOC 25.0% (as supplied)
5.0% (1:4)
40 CFR PART 59 SUBPART C 2.8% (1:8)
2.3% (1:10)

Fragrance None added

Shelf Life 2 years
ASTM D1791-93

Density 8.6 lb/gal (@ 68°F)
1.03 kg/L (@ 20°C)
ASTM D1475 D-13

DIRECTIONS

1. Mix stripper per the dilution listed on the label.
2. Apply solution liberally to the floor and allow to soak for 10 minutes ensuring the solution does not dry.
3. Scrub floor with automatic scrubber or stripping machine. Pick up dirty solution with automatic scrubber or wet vac.
4. Rinse thoroughly with clean water and allow floor to dry completely before applying any finish.

Note: Test floor for color fastness in an inconspicuous area.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com



Product Code	522FS	522MP	522FSC	522MPC
Volume	2.50 US gallons	1.06 US gallons	2.50 US gallons	1.06 US gallons
Shipping Package	2 x 2.5 gallons	4 x 1.06 gallons	2 x 2.5 gallons	4 x 1.06 gallons
Pallet Quantity	48	48	48	48

-522_PDS 06/24