

255FP0 ORBITAL FLOOR MACHINE

A versatile high-speed orbital floor machine with improved isolator design providing smooth operation and increased durability.



WHY THE 255FP0:

VERSATILE

- VCT stripping (wet or dry)
- Scrubbing and deep scrubbing
- Deep cleaning
- Polishing (wet or dry)
- Buffing
- Wood floor sanding and abrading

PRODUCTIVE

- 120V 1.5 HP totally enclosed motor
- 14" x 20" (35.6 cm x 50.8 cm) pad size
- 3,600 orbits per minute
- 50 foot (15 m) UL listed 12/3 SJO power cord with hospital grade plug
- Optional 2.5 gal. (9.5 liter) solution tank
- Isolators deliver 3X greater durability than the leading competitor.

USER FRIENDLY OPERATION

- Four isolators for reduced vibration and easier operation
- Adjustable, anti-fatigue soft-touch handle
- Larger 6" wheels for easier maneuverability
- Lowered wheel position provides extra stability and vibration dampening
- Dual lever on/off safety switch for left or right hand operation
- Dust containment kit
- Standard active vac mounted above the motor to improve balance and reduce operator fatigue

SURFACES

VCT/LVT

CONCRETE

TERRAZZO

TILE

WOOD

CARPET



255FP0 ORBITAL FLOOR MACHINE

SPECIFICATIONS

255FP01420	
Pad Size	14" x 20" (35.6 cm x 50.8 cm)
Pad Speed	3,600 orbits/minute
Base Weight w/o Weights	105 lbs (47.6 kg)
Total Assembled Weight	145 lbs (65.8 kg)
Noise Level	69 dB(A)
Solution Tank (Optional)	2.5 gal (9.5 liter)
Motor	3450 rpm 1.5hp
Power Cord	50' (15m)/12 gauge
Wheels	6" x 2" (15.2 cm x 5 cm)
Warranty	1 Year parts and labor. See manual for full warranty details.

