

Conforms to 1907/2006/EC - (EU) 2015/830

Issued: Sept. 21, 2016 Supersedes: May 20, 2015

FINAL STRIP HD FLOOR STRIPPER

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 PRODUCT IDENTIFIER

> Product Name: Final Strip H.D. (Heavy Duty) Floor Stripper **Product Number:** 502

RELEVENT IDENTIFIED USES OF THE MIXTURE AND USES ADVISED AGAINST 1.2

Product intended for commercial and industrial use only. Intended Use: Floor finish remover concentrate Uses Advised Against: Other than per labelled instructions.

1.3 **DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET**

Manufacturer:

Amano Pioneer Eclipse Corporation

P.O. Box 909 1 Eclipse Road Sparta, NC 28675

Telephone: 1-336-372-8080 Email: sds@pioneereclipse.com Internet: www.pioneereclipse.com

EMERGENCY TELEPHONE NUMBER 1.4

> For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident. Call CHEMTREC Day or Night. Within USA and Canada 1-800-424-9300. Outside USA and Canada 1-703-527-3887 (collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

CLASSIFICATION OF THE MIXTURE 2.1

This mixture has been classified according to EC 1272/2008.

Skin Corrosion - Category 1B Eye Damage - Category 1

Specific Target Organ Toxicity (Single Exposure) - Category 3

2.2 **LABEL ELEMENTS**

> Signal Word: Danger

Hazard pictogram(s):



Hazard Statement(s):

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

Precautionary Statement(s):

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection. P310 Immediately call a POISON CENTER/doctor if you feel unwell.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor. P301+P330+P331 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P303+P361+P353

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

2.3 **OTHER HAZARDS** No other hazards are known to the supplier



Conforms to 1907/2006/EC - (EU) 2015/830

Issued: Sept. 21, 2016 Supersedes: May 20, 2015

FINAL STRIP HD FLOOR STRIPPER

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1/3.2 SUBSTANCES/MIXTURES

				CLP Classification	
Ingredient	EC No.	Weight %	CAS No.	Hazard Class	Hazard Statement(s)*
ethylene glycol monobutyl ether	203-905-0	10 - 30	111-76-2	Acute Tox 4 Eye Irrit 2 Skin Irrit 2	H302,H312,H332 H319 H315
ethanolamine	205-483-3	5 - 10	141-43-5	Acute Tox 4 Skin Corr 1B STOT SE 3	H302,H312,H332 H314 H335

^{*}See section 16 for the full text of R phrases and Hazard Statements

SECTION 4: FIRST AID MEASURES

4.1 DECRIPTION OF FIRST AID MEASURES

Eye Contact: Immediately wash out with water for at least 15 minutes. (If easy to do, remove contact lenses, if

worn.) Seek medical attention immediately.

Skin Contact: Immediately wash with plenty of water for at least 15 minutes. (Remove any contaminated clothing

and shoes.) Seek medical attention immediately.

Inhalation: If breathing is difficult: Remove to fresh air. Seek medical attention immediately.

Ingestion: Call a physician or poison control center immediately. DO NOT induce vomiting unless directed to

do so by medical personnel. Never give anything by mouth to an unconscious person.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Eye Contact: Causes serious eye damage. May cause permanent damage.

Skin Contact: Causes skin burns. May cause permanent damage.

Inhalation: May cause irritation and corrosive effects to nose, throat and respiratory tract.

Ingestion: May cause burns to mouth, throat and stomach.

4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

No information available.

SECTION 5: FIRE FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

In case of fire: use dry chemical, water spray, foam, carbon dioxide

5.2 SPECIAL HAZARDS ARISING FROM THE MIXTURE

Hazardous combustion products: CO, CO₂

During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include but not limited to the above mentioned substances.

5.3 ADVICE FOR FIRE FIGHTERS

As in any fire, wear self contained breathing apparatus and suitable protective clothing including gloves and eye/face protection. Fire-fighters should wear clothing conforming to EN469 for chemical incidents. Materials can splatter above 100°C/212°F. Corrosive material.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Refer to Section 8 for appropriate personal protective equipment.

6.2 ENVIRONMENTAL PRECAUTIONS

Keep spills and cleaning runoff out of sewers and open bodies of water.



Conforms to 1907/2006/EC - (EU) 2015/830

Issued: Sept. 21, 2016 Supersedes: May 20, 2015

FINAL STRIP HD FLOOR STRIPPER

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Small spills: Absorb spill on inert material (e.g. sand, earth) and dispose of as waste material in accordance with national and regional provisions.

Large spills: Keep spectators away. Floors may be slippery; use care to avoid falling. Neutralize spill area. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal.

6.4 REFERENCE TO OTHER SECTIONS: Refer to Section 8 of the SDS.

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Use only in well-ventilated areas. Avoid breathing vapours or spray mists. Remove and wash contaminated clothing and footwear before re-use.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage temperature (Max. 60°C/140°F) (Min. 1°C/34°F). Keep from freezing. Keep container sealed when not in use. Keep out of reach of children.

7.3 SPECIFIC END USE(S): No information available

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Workplace Exposure Limits:

Ingredient	Source	TWA (8hours)		STEL (Short term)		Note(s)
Ingredient	Source	ppm	mg/m ³	ppm	mg/m ³	14016(3)
	ACGIH TLV	20	97	-	-	BEI
	DE (TRGS 900)	-	-	10	49	H,Y, AGS
ethylene glycol monobutyl ether	DK - At-Vejledning Stoffer og materialier- C.0.1	20	98	-	-	EH
	EU (2000/39/EC)	20	98	50	246	Skin
	NO – Forskrift, best.nr. 704	-	-	10	50	Н
	EH40	25	123	50	246	Sk, BMGV
	1	T14/4 /	٠, ,	OTE: (0)		

Ingredient	Source	TWA (8	TWA (8hours)		STEL (Short term)	
ingredient	Source	ppm	mg/m³	ppm	mg/m³	Note(s)
	ACGIH TLV	3	7.5	6	15	ı
	DE (TRGS 900)	-	-	2	5.1	H,Y,Sh
	DK - At-Vejledning Stoffer og					
ethanolamine	materialier- C.0.1	1	2.5	-	-	Н
	EU (2006/15/EC)	1	2.5	3	7.6	Skin
	NO Administrative Norm	1	2.5	-	-	Н
	EH40	1	2.5	3	7.6	Skin

8.2 EXPOSURE CONTROLS

Engineering Controls: Use only with adequate ventilation. Use local ventilation and other engineering controls to maintain

airborne contaminants below established and recommended exposure limits. If this product contains ingredients with exposure limits, monitoring may be required to determine the effectiveness

of ventilation and other control measures.

Environmental exposure controls: No specific environmental exposure controls known.

Personal Protective Equipment (PPE)

Eye/Face Protection: Safety eyewear is recommended to avoid chemical splashes and mists.

Safety glasses or goggles (EN166).



Conforms to 1907/2006/EC - (EU) 2015/830

Issued: Sept. 21, 2016 Supersedes: May 20, 2015

FINAL STRIP HD FLOOR STRIPPER

Hand Protection: Chemical resistant gloves are recommended. (EN374).

Protective index 6, Breakthrough time > 480 mins. (E.g. - nitrile gloves, 0.4 mm thickness)

Protective gloves should be selected according to the application and duration of use. Workplace selection should take into consideration handling requirements, physical requirements and exposure

to other substances.

Skin Protection: If major exposure is possible, wear suitable protection such as rubber boots, apron, etc.

Respiratory Protection: Respiratory protection should be worn when there is a potential of inadequate ventilation. If

exposure limits are exceeded or symptoms are experienced, use an approved respirator with multi-

purpose combination filter. (E.g. - EN 14387- ABEK)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance: clear, red, liquid
Odor: slight lemon

Odor Threshold: No test data available

pH: 12.6 (as supplied) [Method: ASTM E 70]

Melting Point/Freezing Point:

No test data available

Initial boiling point/boiling range: No test data available

Flash Point: > 93°C [Method: Closed cup, ASTM D 56]

Evaporation Rate:

Flammability (solid, gas)

Upper/lower flammability/explosive limits:

Vapor Pressure:

Vapor Density:

No test data available

No test data available

No test data available

No test data available

Relative Density: 1.0 kg/L @ 20°C [Method: Pycnometer, ASTM D 1475]

Solubility: miscible in water
Partition Coefficient (n-octanol/water): No test data available
Auto Ignition temperature: No test data available
Decomposition Temperature: No test data available

Viscosity: < 5 centipoise @ 20°C [Method: Rotational viscometer, Brookfield]

Explosive Properties: none Oxidizing properties: none

9.2 OTHER INFORMATION

VOC: 33%(as supplied), 6.5%(1:4), 3.6%(1:8), 2.9%(1:10)

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY: None known

10.2 CHEMICAL STABILITY: Stable under normal conditions.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS: Product may react strongly with water. Care should be used if diluting;

product should be slowly added to water.

10.4 CONDITIONS TO AVOID: None known

10.5 INCOMPATIBLE MATERIALS: Strong acids, bases and oxidizing agents. Do not mix with other chemicals

unless stated on the product label.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS: None known

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY: Toxicity testing has not been completed on the mixture.

Based on available data, the classification criteria are not met.





Conforms to 1907/2006/EC - (EU) 2015/830

Issued: Sept. 21, 2016 Supersedes: May 20, 2015

FINAL STRIP HD FLOOR STRIPPER

ATE $_{mix}$ (oral): > 2000 mg/kg ATE $_{mix}$ (dermal): > 2000 mg/kg

ATE $_{mix}$ (inhalation): > 20 mg/l (4 hr/vapour)

Component	CAS#	LD50 Oral- Rat (mg/kg)	LD50 Dermal - Rabbit (mg/kg)	LC50 Inhalation- rat (mg/l)
ethylene glycol monobutyl ether	111-76-2	1300	2000	guinea pig (1hr), >3.1
ethanolamine	141-43-5	1515	2504	(4hr), >1.3

SKIN CORROSION/IRRITATION: Causes severe skin burns.

Classified as Skin Corrosive - Category 1B

SERIOUS EYE DAMAGE/IRRITATION: Causes serious eye damage.

Classified as Eye Damage - Category 1

RESPIRATORY OR SKIN SENSITIZATION:

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

STOT-SINGLE EXPOSURE: Classified as STOT-SE - Category 3
May cause respiratory irritation.

May cause respiratory irritation.

Based on available data, the classification criteria are not met.

ASPIRATION HAZARD: Based on available data, the classification criteria are not met.

11.2 POTENTIAL ADVERSE HEALTH EFFECTS

Effects and symptoms related to this mixture, if any, are listed in Section 4.2.

SECTION 12: ECOLOGICAL INFORMATION

STOT-REPEATED EXPSURE:

12.1 TOXICITY: Ecological testing has not been completed on the mixture.

Component	CAS#	LC50	LC50	EC50 - 72 hr
ethylene glycol monobutyl ether	111-76-2	vertebrate, 820-1490 mg/ml	Daphnia magna, 835 mg/l	algae, 911 mg/l
ethanolamine	141-43-5	vertebrate, 125-2010 mg/ml	Daphnia magna, 33-93 mg/l	algae, 2.5 mg/l

12.2 PERSISTANCE AND DEGRADABILITY: Testing has not been completed on the mixture.

Component	CAS#	Biodegradation
ethylene glycol monobutyl ether	111-76-2	readily biodegradable
ethanolamine	141-43-5	readily biodegradable

12.3 BIOACCUMULATIVE POTENTIAL: Testing has not been completed on the mixture.

		Partition coefficient n-	
Component	CAS#	octanol/water (Log	Bioconcentration factor
-		Kow)	(BCF)
ethylene glycol monobutyl ether	111-76-2	0.81	< 100
ethanolamine	141-43-5	-1.91	< 100

12.4 MOBILITY IN SOIL: Testing has not been completed on the mixture.

Component	CAS#	Soil Organic Carbon- Water Partitioning Coefficient (Koc)
ethylene glycol monobutyl ether	111-76-2	67
ethanolamine	141-43-5	1.17



Conforms to 1907/2006/EC - (EU) 2015/830

Issued: Sept. 21, 2016

Supersedes: May 20, 2015

FINAL STRIP HD FLOOR STRIPPER

12.5 RESULTS OF PBT AND vPvB ASSESSMENT: Not applicable

12.6 OTHER ADVERSE EFFECTS: No data available

12.7 ADDITIONAL INORMATION: Based on available data, the classification criteria are not met.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Disposal of this material should be in accordance with local, regional and national regulations.

EU Waste Catalogue: 20 01 15* - alkalines

SECTION 14: TRANSPORT INFORMATION

14.1 UN NUMBER: UN1760

14.2 UN PROPER SHIPPING NAME: Corrosive liquid, n.o.s. (ethanolamine)

14.3 TRANSPORT HAZARD CLASSES: 8

14.4 PACKING GROUP: III

14.5 ENVIRONMENTAL HAZARDS: N/A

14.6 SPECIAL PRECAUTIONS FOR USER:

Package volumes < 5 L are shipped as Limited Quantity; as permitted by hazard class and quantity limits.

IMDG

Emergency Schedules (EmS): Fire F-A, Spillage S-B

Stowage and Segregation: Category A. Clear of living quarters.

Marine Pollutant: None

ADR/RID

Class: 8
Item Number: 80
Classification Code C9

14.7 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MAPROL73/78 AND THE IBC CODE: N/A

SECTION 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE MIXTURE

EINECS STATUS: Ingredients are included in the EINECS/ELINCS/NLP inventories.

NATIONAL REGULATIONS: No additional national regulations are known to the supplier.

15.2 CHEMICAL SAFETY ASSESSMENT: No information available.

SECTION 16: OTHER INFORMATION

REVISION INFORMATION:

Sept. 21, 2016 - Logo, email address, Revisions per 2015/830, Revisions Section 2.2, 10.5, 11.1, 16

ABBREVIATIONS:

N/A - Not applicable

N/E - Not Established

N/L - Not Listed

FULL TEXT OF HAZARD STATEMENTS:

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.



Conforms to 1907/2006/EC - (EU) 2015/830

Issued: Sept. 21, 2016 Supersedes: May 20, 2015

FINAL STRIP HD FLOOR STRIPPER

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

FULL TEXT OF PRECAUTIONARY STATEMENTS:

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.
P312 Call a POISON CENTER/doctor if you feel unwell.

P321 Specific treatment (see ... on this label).

P337+313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P403+233 Store in well ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

ISSUED BY:

Chemical/R&D Department

Amano Pioneer Eclipse Corporation