

Diamond Shine™

ULTRA HIGH SPEED FLOOR COATING



A budget-friendly UHS finish that provides a wet-look shine and superior scuff resistance.

SURFACES



WHY DIAMOND SHINE:

OUR BEST BLACK HEEL MARK RESISTANCE - FEWER BURNISHINGS

Durable wax blend

ACCELERATED DRY TIME

18% Non-Volatile Solids

REPAIRABLE HIGH GLOSS SHINE

Acrylic co-polymer

PRODUKTDATEN

Beschreibung	Polymer emulsion
Farbe	weiß (milchig)
Glanzkapazität (60°) ASTM D1455-87 (2008)	>85
Viskosität (Brookfield) @ 68°F (20°C)	<10 centipoise
Deckung	2500 to 3000 ft ² /gal 61 to 74 m ² /liter
Trocknungszeit	About 30 minutes
Buffability	ausgezeichnet
Entfernbarkeit ASTM D1792-06	ausgezeichnet
FOV 40 CFR Part 59 Subpart C	0.06%
Total Solids	24%
Feste Bestandteile ASTM D2834-95 (2008)	18%
Duft	etwas ammoniakalisch
Rutschbeständigkeit ULTM410	klassifiziert
Haltbarkeit ASTM D1791-93 (2008)	1 Jahr
Dichte ASTM D1475-98 (2008)	8.6 lb/gal @ 68°F 1.03 kg/L @ 20°C
Reinigungsmittel- widerstandsfähigkeit ASTM D3207-92 (2008)	ausgezeichnet
Gefrier-/Siedepunkt ASTM D3209-93 (2008)	widersteht 3 Zyklen

DISINFECTANT COMPATIBILITY:

The following Pioneer Eclipse disinfectants are safe to use on this floor coating when correctly diluted and used according to the product directions. Bleach and other corrosives may cause damage.

Nova Disinfectant

MeridiClean All Purpose Cleaner & Disinfectant

NeutraQuat 256 Germicidal Disinfectant

Triton XLC Bathroom Cleaner & Disinfectant

ANWENDUNG

Apply thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com



Klassifiziert beim U.L. betreffender Rutschbeständigkeit. 42E6

Produktnummer	104FS	104MPE	104DR
Inhalt	2.50 US gallons	4 liters	55 US gallons
Größe	2 x 2.5 gallons	4 x 4 liters	1 x 55 gallons
Palettenmenge	48	48	4