

Apollo™

PREMIUM FLOOR COATING

An ultra high solids UHS finish with superior flow characteristics for easy and efficient application.



**No Intentionally
Added PFAS**

SURFACES



WHY APOLLO:

**FEWER COATS NEEDED =
LABOR SAVINGS**

28% Non-Volatile Solids

REPAIRABLE

Acrylic co-polymer blend

**EXCELLENT FLOW - FEWER
MISAPPLICATIONS**

Formulated for ease of use

TECHNICAL DATA

Description	Polymer emulsion
Appearance	Milky white
Specular Gloss (60°) ASTM D1455-87 (2008)	>85
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise
Coverage Rate	2000 to 2500 ft ² /gal 49 to 61 m ² /liter
Dry Time	About 30 minutes
Buffability	Excellent
Removability ASTM D1792-06	Excellent
VOC 40 CFR Part 59 Subpart C	0.06%
Total Solids	35%
Non-Volatile Solids ASTM D2834-95 (2008)	28%
Fragrance	Mild odor
Slip Resistance ULTM410	UL pending
Shelf Life ASTM D1791-93 (2008)	1 year
Density ASTM D1475-98 (2008)	8.7 lb/gal @ 68°F 1.04 kg/L @ 20°C
Detergent Resistance ASTM D3207-92 (2008)	Excellent
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

DISINFECTANT COMPATIBILITY:

The following Pioneer Eclipse disinfectants are safe to use on this floor coating when correctly diluted and used according to the product directions. Bleach and other corrosives may cause damage.

MeridiClean All Purpose Cleaner & Disinfectant

NeutraQuat 256 Germicidal Disinfectant

Triton XLC Bathroom Cleaner & Disinfectant

DIRECTIONS

Apply thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com

CARB
Compliant

Product Code	147FS	147MPE	147DR
Volume	2.50 US gallons	4 liters	55 US gallons
Shipping Package	2 x 2.5 gallons	4 x 4 liters	1 x 55 gallons
Pallet Quantity	48	48	4