

Eclipse™

HARD FLOOR SEALER



Ideal for concrete, terrazzo, marble and similar hard surfaces.
Also suitable for VCT, vinyl and similar resilient surfaces.

SURFACES



WHY ECLIPSE HARD FLOOR SEALER:

EXCELLENT STAIN RESISTANCE

INCREASED ADHESION

RESISTS CHIPPING, FLAKING

LOW ODOR

CLEAR ON FLOOR

TECHNICAL DATA

Description	Polymer emulsion
Appearance	Milky white
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise
Coverage Rate	1500 ft ² /gal first coat 37 m ² /l 2500 to 3000 ft ² /gal 61 to 74 m ² /liter
Dry Time	About 30 minutes
Removability ASTM D1792-06	Excellent
VOC 40 CFR Part 59 Subpart C	0.04%
Non-Volatile Solids ASTM D2834-95 (2008)	22%
pH ASTM E70-07	9.3
Fragrance	Mild Acrylic
Slip Resistance ULTM410	UL pending
Shelf Life ASTM D1791-93 (2008)	1 year
Density ASTM D1475-98 (2008)	8.5 lb/gal @ 68°F 1.02 kg/L @ 20°C
Detergent Resistance ASTM D3207-92 (2008)	Excellent
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

DIRECTIONS

Apply thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com



UL pending

42E6

Product Code	403FS	403MPE
Volume	2.50 US gallons	4 liters
Shipping Package	2 x 2.5 gallons	4 x 4 liters
Pallet Quantity	48	48