

EclipseTM CERAMIC RESTORER

A high-performance penetrating sealer to protect ceramic from damage & dirt penetration and restore gloss.



WHY ECLIPSE:

UNIQUE SILICATE BLEND CREATES A SURFACE THAT IS:

- BREATHABLE
- ULTRA-HARD
- WATER/DUST REPELLENT

GUARDS AGAINST STAINS

CAN BE BURNISHED TO A HIGH GLOSS



TECHNICAL DATA

Description	Ceramic restorer
Appearance	Milky, white
рН АSTM E70-07	10.5
Flash Point	>200°F (93°C)
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise @ 68ºF (20ºC)
Coverage Rate	3000 - 4000 ft²/gal 74 - 100 m²/liter
VOC 40 CFR Part 59 Subpart D	<100 g/L
Fragrance	No added fragrance
Shelf Life ASTM D1791-93 (2008)	1 year
Density ASTM D1475-13 (2008)	8.4 lb/gal @ 68°F 1.01 kg/L @ 20°C
Solubility	Miscible in water
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

DIRECTIONS

NOTE: Do not apply Eclipse Ceramic Restorer on floors previously treated with other guards or sealers.

Apply with a pump-up sprayer. Spread evenly with a clean micro-fiber applicator. Allow to dry thoroughly and burnish with a hair blend pad. Repeat with a second coat.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com

Product Code458CFSEVolume10 litersShipping Package2 x 10 litePallet Quantity48

458C_PDS 10/20