



Formula X™ UHP

ULTRA HIGH PERFORMANCE STRIPPER



Fast acting **Formula X Ultra High Performance Stripper** is a powerful, non-ammoniated formula that cuts through heavy build-up and hard to remove water-based sealers in record time.

DIRECTIONS

Read all directions and Safety Data Sheet (SDS) before using.

- Mix stripper per the following dilutions:
For sealer & coating removal:
1:4 (250 ml per 1 liter of water).
For coating removal only:
1:8 (125 ml per 1 liter of water).
- Apply solution liberally to the floor and allow to soak for 10 minutes ensuring the solution does not dry.
- Scrub floor with automatic scrubber or stripping machine. Pick up dirty solution with automatic scrubber or wet vac.
- Rinse thoroughly with clean water or use EnviroStar Green All Purpose Neutralizer per label instructions. Allow floor to dry thoroughly.

Note: Test surface for color fastness in an inconspicuous area.

PRODUCT INFO

Product Code 503L5

Volume 5 liters

Shipping Package 2 x 5 liters

Pallet Quantity 64 cases

SURFACES

All resilient tile flooring ("VCT), and most types of terrazzo, marble and quarry tile.

Not recommended for asphalt, rubber or asbestos tile flooring.



TECHNICAL DATA

Description	Non-ammoniated, ultra high performance stripper
Appearance	Clear liquid
Fragrance	No added fragrance
Flash Point <small>(ASTM D1792-06)</small>	>93°C
Viscosity (Brookfield) <small>@ 68°F (20°C)</small>	<10 mPa.s
Shelf Life <small>ASTM D1791-93 (2008)</small>	2 years
Density <small>ASTM D1475-13 (2008)</small>	+/- 0.99 g/cm ³
Freeze/Thaw <small>ASTM D3209-93 (2008)</small>	Passes 3 cycles ASTM D3209-93 (1998)
VOC <small>40 CFR Part 59 Subpart D</small>	+/- 42%

SDS available for download at www.pioneereclipse.com

