Helios H106[™] **FLOOR COATING**

A durable, scuff-resistant floor coating specifically designed to rejuvenate and protect LVT and other low maintenance flooring.

WHY HELIOS H106 FLOOR COATING:

VERSATILE COATING FOR USE ON MOST COMMERCIAL FLOOR TYPES

Ideal for LVT and other factory coated flooring materials

HIGHLY RESISTANT TO SCUFF AND **BLACK HEEL MARKS**

Durable polymer and wax blend

NO INTENTIONALLY ADDED PFAS No fluorosurfactants

MATTE FINISH INCLUDES NANO-CERAMIC MATTING TECHNOLOGY

Floors won't burnish due to traffic patterns or maintenance

DIRECTIONS

Apply thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com

roduct Code	106HGFS	106HGMPE	106MFS	106MMPE	
olume	2.50 US gallons	1.06 US gallons	2.50 US gallons	1.06 US gallons	
hipping Package	2 x 2.5 gallons	4 x 1.06 gallons	2 x 2.5 gallons	4 x 1.06 gallons	
allet Quantity	48	48	48	48	



TECHNICAL DATA

Description	Polymer emulsion		
Appearance	Milky white		
Specular Gloss (60°) ASTM D1455-17	High gloss >80 Matte <35		
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise		
Coverage Rate	2500 to 3000 ft²/gal 61 to 74 m²/liter		
Buffability	High gloss - Excellent Matte - n/a		
Dry Time	About 20 minutes		
Removability ASTM D1792-17	Excellent		
VOC 40 CFR Part 59 Subpart C	<0.2%		
Fragrance	Mild odor, no fragrance added		
Slip Resistance	Meets requirements		
Shelf Life ASTM D1791-93 (2008)	1 year		
Density	High gloss 8.5 lb/gal @ 68°F 1.02 kg/L @ 20°C		
ASTM D1475-13	Matte 8.6 lb/gal @ 68°F 1.03 kg/L @ 20°C		
Detergent Resistance ASTM D3207-17	Excellent		
Freeze/Thaw ASTM D3209-93	Passes 3 cycles		
Floor Coating and Finishing materials as to slip resistance only. 42E6			



106_PDS 5/25

Pioneer

LVT

VCT

LINOLEUM

ARMOLEU

DISINFECTANT COMPATIBILITY:

The following Pioneer Eclipse

MeridiClean All Purpose Cleaner &

NeutraQuat 256 Germicidal Disinfectant

Disinfectant

Pr Vo Sh

disinfectants are safe to use on this floor coating when correctly diluted and used according to the product directions. Bleach and other corrosives may cause damage.

Eclipse