


400BU PROPANE FLOOR BURNISHER



Pad Size 21" (53 cm) 28" (71 cm) **Pad Speed** 2000 rpm 1500 rpm



WHY 400BU:

RELIABLE PERFORMANCE

- Powerful 18 HP 603cc propane engine with EPS[™] technology
- "Hot @ 4 o'clock" set up provides true and straight operation
- Soft tread adjustable wheels for smooth operation

DESIGNED FOR SAFETY

- SAFR Technology keeps emissions low even when air filter is dirty
- Muffler system exceeds EPA and CARB minimum requirements

COST EFFECTIVE

- Uses 34% LESS fuel than other machines in its class
- 5 Times LONGER oil change interval than other machines in its class

EASY TO USE & MAINTAIN

- Easy pad changes with Rok-Bak[™] engineering
- Easy access battery service and oil changes



Pioneer Eclipse proprietary Safer Air Fuel Ratio (SAFR) fuel system technology is a closed-loop system that maintains an optimal air-to-fuel ratio even under harsh conditions. SAFR technology helps to keep dangerous Carbon Monoxide (CO) output low, and your operators safe.









400BU_PDS 11/19



SPECIFICATIONS

	400BU21	400BU28
Performance	25,000 ft ² /hr (2300 m ² /hr)	34,000 ft ² /hr (3160 m ² /hr)
Pad Size	21" (53 cm)	28" (71 cm)
Pad Speed	2000 rpm	1500 rpm
Engine	603 cc	603 cc
Noise Level	< 89 db(A)	< 89 db(A)
Width	22.8 in (58 cm)	32.5 in (83 cm)
Weight	187 lb (85 kg)	200 lb (91 kg)
Warranty	Engine: Parts & Labor - 2 yrs. Machine: Excludes wear and maintenance items.	Parts & Labor - 1 yr.

AVAILABLE MODELS

	Size	Battery Start	Steel Tank	Clutch	EcoSense
400BU21BM	21" (53 cm)	•			
400BU21BSM	21" (53 cm)	•	•		
400BU21BSMX	21" (53 cm)	•	•		•
400BU21BCSM	21" (53 cm)	•	•		
400BU28BM	28" (71 cm)	•			
400BU28BSM	28" (71 cm)	A •	•		
400BU28BSMX	28" (71 cm)	•	•		•
400BU28BCSM	28" (71 cm)	•	•	•	

400BU_PDS 11/19