

440BU PROPANE FLOOR BURNISHER

A **premium burnisher** fully optioned to satisfy floor care professionals around the world.

Pad Size 21" (53 cm) 24" (61 cm) 28" (71 cm) Pad Speed 2000 rpm 1800 rpm 1500 rpm



RELIABLE PERFORMANCE

- Powerful 18 HP 603cc propane engine with EPS™ technology
- Cowl design keeps engine cooler for longer life
- "Hot @ 4 o'clock" set up provides true and straight operation
- Heavy duty casters and wheels for added durability
- Standard dust control
- Premium pad holder for improved burnish response
- Larger air filter area stays cleaner longer

DESIGNED FOR SAFETY

- Operator Presence automatic shutoff system
- SAFR™ Technology keeps emissions low even when air filter is dirty
- SafeSense[™] emmissions monitoring
- Muffler system w/heat shield, exceeds EPA and CARB minimum requirements

COST EFFECTIVE

- Uses 34% LESS fuel than other machines in its class
- 5 Times LONGER oil change interval than other machines in its class

EASY TO USE & MAINTAIN

- Easy pad changes with Rok-Bak™ engineering
- Adjustble ergonomic handle for improved operator comfort









440BU_PDS 11/19



Pioneer Eclipse proprietary **Safer Air Fuel Ratio** (SAFR) fuel system technology is a closed-loop system that maintains an optimal air-to-fuel ratio even under harsh conditions. SAFR technology helps to keep dangerous Carbon Monoxide (CO) output low, and your operators safe.



SPECIFICATIONS

	440BU21	440BU24	440BU28
Performance	25,000 ft ² /hr (2300 m ² /hr)	28,000 ft²/hr (2600 m²/hr)	34,000 ft ² /hr (3160 m ² /hr)
Pad Size	21" (53 cm)	24" (61 cm)	28" (71 cm)
Pad Speed	2000 rpm	1800 rpm	1500 rpm
Engine	603 cc	603 cc	603 cc
Noise Level	< 89 db(A)	< 89 db(A)	< 89 db(A)
Width	24.5 in (62 cm)	27.5 in (70 cm)	31.5 in (80 cm)
Neight	242 lb (97 kg)	248 lb (100 kg)	262 lb (119 kg)

AVAILABLE MODELS

	Size	Battery Start	Clutch	Steel Tank	Dust Control	SafeSense
440BU21	21" (53 cm)	•	•	•	•	•
440BU24	24" (61 cm)	•	•	•	•	•
440BU28	28" (71 cm)	•	•	•	•	•

440BU_PDS 11/19